Generic Calorimeter Tower

•••

Nils Feege, Jin Huang November 17, 2015

Objective:

A generalized calorimeter description, which supports both forward and central calorimeters.

g4cemc/RawTowerDefs.h

```
+ /*! Convert name string to calorimeter ID
+ */
+ inline RawTowerDefs::CalorimeterId
+ convert_name_to_caloid(const std::string caloname)
+ {
+ if (caloname == "NONE")
+ return NONE;
+
+ else if (caloname == "CEMC")
+ return CEMC;
+
+ else if (caloname == "HCALIN")
+ return HCALIN;
```

```
/*! Extract tower index 1 of calorimeter tower from CaloTowerID
    */
inline unsigned int
decode_index1(const unsigned int calo_tower_id)
{
    return (calo_tower_id >> RawTowerDefs::index1_idbits) & 0xFFF;
}

/*! Extract tower index 2 of calorimeter tower from CaloTowerID
    */
inline unsigned int
decode_index2(const unsigned int calo_tower_id)
{
    return calo_tower_id & 0xFFF;
}
```

g4cemc/RawTowerGeom.h g4cemc/RawTowerGeomv1.h

```
+class RawTowerGeomv1 : public RawTowerGeom {
  public:
  RawTowerGeomv1(RawTowerDefs::keytype id);
   virtual ~RawTowerGeomv1();
   void identify(std::ostream& os=std::cout) const;
   RawTowerDefs::keytype get_id() const { return _towerid;}
   void set center x( double x ) { center x = x; return ; }
   void set_center_y( double y ) { _center_y = y; return ; }
   void set_center_z( double z ) { _center_z = z; return ; }
   double get_center_x() const { return _center_x; }
   double get_center_y() const { return _center_y; }
   double get_center_z() const { return _center_z; }
   double get center radius() const;
   double get_eta() const;
   double get phi() const;
```

g4cemc/RawTowerGeomContainer.h g4cemc/RawTowerGeomContainerv1.h

```
+class RawTowerGeomContainerv1 : public RawTowerGeomContainer
+{
+ public:
  RawTowerGeomContainerv1( RawTowerDefs::CalorimeterId caloid );
  virtual ~RawTowerGeomContainerv1():
  void Reset();
  int isValid() const;
  void identify(std::ostream& os=std::cout) const;
  void set_calorimeter_id( RawTowerDefs::CalorimeterId caloid ) { _caloid = caloid; }
   RawTowerDefs::CalorimeterId get_calorimeter_id() const { return _caloid; }
  Constiturator add_tower_geometry(RawTowerGeom *geo);
   RawTowerGeom *get_tower_geometry(RawTowerDefs::keytype key);
  //! return all tower geometries
  ConstRange get tower geometries( void ) const;
  Range get tower geometries ( void );
```

g4cemc/RawTowerGeomContainer_Cylinderv1.h

```
std::pair<double, double>
get_phibounds(const int ibin) const;
std::pair<double, double>
get_etabounds(const int ibin) const;
double
get_etacenter(const int ibin) const;
double
get_phicenter(const int ibin) const;
int
get_etabin(const double eta) const;
int
get_phibin(const double phi) const;
```

g4cemc/RawTowerBuilder.cc (Cylinder calorimeter)

The tower builder classes also construct the tower geometries.

```
rawtowergeom->set_radius(inner_radius);
rawtowergeom->set_thickness(thickness);
rawtowergeom->set_phibins(_nphibins);
+// rawtowergeom->set_phistep(_phistep);
+// rawtowergeom->set_phimin(_phimin);
rawtowergeom->set_etabins(_netabins);
```

g4cemc/RawTowerBuilderByHitIndex.h

Currently: Read geometry from text file. Possible updates: Let G4Detector module write geometry file? Use database?

```
+class RawTowerBuilderByHitIndex : public SubsysReco {
+public:
   RawTowerBuilderByHitIndex( const std::string& name="RawTowerBuilderByHitIndex" );
   virtual ~RawTowerBuilderByHitIndex(){}
   int InitRun(PHCompositeNode *topNode);
   int process event(PHCompositeNode *topNode);
   int End(PHCompositeNode *topNode);
   /** Name of the detector node the G4Hits should be taken from.
   void Detector( const std::string &d );
   /** Specifiy text-file with table for tower mapping
   void GeometryTableFile( const std::string d )
   { mapping_tower_file_ = d; }
```

g4cemc/RawTowerDigitizer.cc

Updated to work for both cylinder and forward geometries.

g4cemc/RawClusterBuilderv1.cc

RawClusterBuilder (current version) only works for cylinder geometries-

Update? Write separate cluster builder for forward detectors?

```
string towergeomnodename = "TOWERGEOM_" + detector;
  RawTowerGeomContainer *towergeom = findNode::getClass<RawTowerGeomContainer>(topNode,
towergeomnodename.c str());
 if (! towergeom)
     cout << PHWHERE << ": Could not find node " << towergeomnodename.c_str() << endl;
       iphi = xcg+0.5;
       dphi = xcg - float(iphi); // this is from -0.5 to +0.5
      phi = towergeom->get_phicenter(iphi);
       std::pair<double, double> phibounds = towergeom->get_phibounds(iphi);
      phistep = phibounds.second - phibounds.first;
      phi += dphi*phistep;
       ieta = ycg+0.5;
```

g4jets/TowerJetInput.C

Now it uses tower x/y/z geometry to calculate eta/phi with the vertex correction, and should be ready to run on forward calorimeters alread

```
@@ -81,14 +83,14 @@ std::vector<Jet*> TowerJetInput::get input(PHCompositeNode *topNode) {
        for (rtiter = begin end.first; rtiter != begin end.second; ++rtiter) {
                                                                                       83
                                                                                               for (rtiter = begin end.first; rtiter != begin end.second; ++rtiter) {
         RawTower *tower = rtiter->second;
                                                                                       84
                                                                                                 RawTower *tower = rtiter->second;
83
                                                                                       85
         double r = geom->get_radius();
                                                                                                 RawTowerGeom * tower geom =
                                                                                                 geom->get_tower_geometry(tower -> get_key());
         int bineta = tower->get_bineta();
                                                                                                 assert(tower geom);
         int binphi = tower->get_binphi();
                                                                                       89
         double eta0 = geom->get_etacenter(bineta);
                                                                                                 double r = tower_geom->get_center_radius();
                                                                                       90
         double phi = geom->get_phicenter(binphi);
                                                                                                 double phi = atan2(tower_geom->get_center_y(), tower_geom-
                                                                                            >get_center_x());
                                                                                       92
                                                                                                 double z0 = tower_geom->get_center_z();
90
                                                                                       93
         double z0 = r * sinh(eta0);
         double z = z0 - vtxz:
                                                                                       94
                                                                                                 double z = z0 - vtxz:
93
                                                                                       95
94
         double eta = asinh(z/r); // eta after shift from vertex
                                                                                       96
                                                                                                 double eta = asinh(z/r); // eta after shift from vertex
```

Retired Classes in g4cemc/

- CrystalCalorimeterDigitization
- CrystalCalorimeterTowerBuilder
- RawTowerBuilderCone
- RawTowerCombiner
- RawTowerv2

Pull request on GitHub (NOT ready for merge, REVIEW only)

https://github.com/sPHENIX-Collaboration/coresoftware/pull/85

